KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

SPK-OCA508

2x20 Watt RMS Powered On-Wall Speaker System

The SPK-OCA508 is a powered two-way speaker system designed for indoor wall mounting. The system accepts a line level stereo input and amplifies it using a built-in amplifier and outputs a speaker signal to the passive speaker.

KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

SPK-OCA508

FEATURES

- Active Loudspeaker - Stereo 2x20W amplifier and volume control.
- Inputs - Line level stereo audio on a 3.5mm connector,
  Stereo audio on a terminal block connector.
- Outputs - Speaker output to passive speaker, Sub-woofer,
  Looping output for chaining to other speaker pairs.
- Magnetically Shielded.
- Enhanced Bass Reflex.
- Auto Power - Shuts off when system is not in use.
- Indoor Wall Mounting.
- Available in Black or White.
- Package - 3m power cord and a loudspeaker cable (in white or black) to link the active loudspeaker with the passive one.

TECHNICAL SPECIFICATIONS

INPUT:	Line level stereo audio on a 3.5mm connector and terminal block connector.
OUTPUTS:	1 speaker (to connect to the external passive speaker), 1 active sub-woofer on a 3.5mm connector, 1 looping output on a 3.5mm connector.
SPEAKER TYPE:	Two-way bass reflex, on-wall speaker.
WOOFER:	5.25” (133mm) polypropylene cone/rubber surround.
TWEETER:	0.75” (20mm) silk dome tweeter.
PASSIVE:	27mm piezo dome.
FREQUENCY RESPONSE:	45Hz to 20kHz.
IMPEDANCE:	8Ω.
SENSITIVITY:	85dB-SPL @1W, 1m.
BUILT-IN POWER AMPLIFIER:	2x20W RMS in active speaker.
CONTROL:	Volume control.
UNIVERSAL POWER SUPPLY:	115 or 220V AC (selectable).
MATERIALS:	Frame, grill and brackets steel; housing ABS.
INSTALLATION CLEARANCE:	Front panel to wall (including mounting bracket): 20cm; back panel to wall (including mounting bracket): 3cm.
DIMENSIONS:	17cm x 19cm x 23.6cm (6.7” x 7.5” x 9.3”) W, D, H.
WEIGHT:	Active speaker 3.57kg (7.87lbs) approx; passive speaker 2.53kg (5.58lbs) approx.
ACCESSORIES:	2 mounting brackets (fixed and rotating), 3m power cord and a loudspeaker cable.